

# RYLTEC FIRE TRUCK

Corrugated SBR rubber mandrel hose with textile reinforcement and steel wire spiral.



Designed for suction and delivery of wastewater, slurry, drains and general applications

With smooth cuffs on both ends for easy coupling

SBR synthetic rubber inner tube resistant to oils in suspension

Manufactured according to ISO 1307

## Colour:

- The standard color is black with blue longitudinal marking.



## Applications:

Designed for suction and delivery of wastewater, slurry, drains and general applications. The hose has smooth cuffs on both ends for easy coupling.

## Construction:

SBR synthetic rubber inner tube, resistant to oils in suspension, with polyester textile reinforcement and steel wire spiral and SBR/EPDM rubber corrugated cover tube.

## Temperature service range:

-30°C (-22°F) to 85°C (176°F)

## Physical properties:

Part number	Nominal Inner Diameter	Smooth cuff ends length	Working Pressure		Burst Pressure		Vacuum	Bending Radius	Nominal Weight	Lenght
	mm	mm	bar	psi	bar	psi	mH2O	mm	kg/m	m
C302102*	102	100	10	150	30	450	9	500	3.40	1-6
C302110	110	110	10	150	30	450	9	550	3.82	1-6
C302152	152	150	5	75	15	225	8	750	5.60	1-6

\*Available on request  
Other diameters also available on request

## tipsa:

reserves the right to modify any specification without prior notice to meet or exceed changing standards. Customers are advised that special diameters or construction characteristics can be produced upon special request. Contact your local dealer or TIPSA at: [tipsaex@tipsa.com](mailto:tipsaex@tipsa.com)